

WARNING

DO NOT EXCEED WORKING LOAD LIMIT.

USE ONLY G80 & G100 COMPATIBLE COMPONENTS FOR OVERHEAD LIFTING .



Safe Lifters

Pundol Apartments, Shop No. 5 & 6, 160 M.G. Road,
Pune - 411001, (India) Tel +91 20 66013783 / 84 / 85 / 86
Fax +91 20 26350832 Email : safelifters@eth.net

Screw Clamp

The SLSC-71 screw clamp is a valuable asset when lifting, pulling and fitting sheet material as well as steel constructions.

Please note that the spindle must be hand-tightened to the material. When the screw clamp is tightened and lifting begins, the pivoting pad clamping system produces a wedging action against the material, holding it securely.



Model	Capacity t	Jaw capacity Z mm	weight kg	A mm	Ø B mm	C mm	D mm	E mm	F mm	G mm
SLSC71	1,5	0 - 35	4,8	191	35	24	15,5	60	105	50
SLSC71	3,0	0 - 35	8,1	235	46	34	17,0	67	120	60
SLSC71	5,0	0 - 40	14,5	275	55	40	17,5	85	150	75
SLSC71	7,5	0 - 40	18,1	295	65	50	22,0	92	162	80

Functional drawing

