

WARNING

DO NOT EXCEED WORKING LOAD LIMIT.

USE ONLY G80 & G100 COMPATIBLE COMPONENTS FOR OVERHEAD LIFTING.

**Safe Lifters**

Pundol Apartments, Shop No. 5 & 6, 160 M.G. Road,
 Pune - 411001. (India) Tel +91 20 66013783 / 84 / 85 / 86
 Fax +91 20 26350832 Email : safelifters@eth.net

Pipe Hooks

The pipe hooks are used in pairs for the safe transport of pipes. The shackles are included with the hooks.

Hooks with a plastic protective cover are available for pipe with sensitive surfaces.

**Pipe Hook for 60°- 90° top angle between chains**

Model	Capacity** t	Weight** kg	t mm	A mm	B mm	C mm	D mm	E mm	F mm	Ø G mm	H mm	Ø I mm	J mm
SLPC68 2/90	2	3,1	20	0 - 40	35	40	62	62	116	16,3	47,6	12,7	30,2
SLPC68 4/90	4	5,6	30	0 - 50	40	48	77	77	142	24,3	72,2	19,0	44,5
SLPC68 6/90	6	10,5	30	0 - 60	51	62	90	90	173	24,3	72,2	19,0	44,5
SLPC68 8/90	8	17,8	40	0 - 70	55	67	105	105	190	30,3	95,3	25,4	58,7
SLPC68 10/90	10	22,0	40	0 - 80	69	80	115	115	221	30,3	95,3	25,4	58,7

Pipe Hook for 90°-120 ° top angle between chains

Model	Capacity** t	Weight** kg	t mm	A mm	B mm	C mm	D mm	E mm	F mm	Ø G mm	H mm	Ø I mm	J mm
SLPC68 2/120	2	3,5	20	0 - 30	34	40	82	75	106	16,3	30,2	12,7	47,6
SLPC68 4/120	4	8,8	30	10 - 40	39	50	95	80	131	24,3	44,5	19,0	72,2
SLPC68 6/120	6	14,9	40	20 - 50	43	55	106	95	153	30,3	58,7	25,4	95,3
SLPC68 8/120	8	18,6	40	30 - 65	54	65	119	100	185	30,3	58,7	25,4	95,3
SLPC68 10/120	10	23,0	50	30 - 75	60	70	143	125	208	36,3	73,0	31,8	117,0

